

STANDARD FEATURES AND SPECIFICATIONS Northwood II...28' Wide Homes

EXTERIOR

Colour coordinated metal fascia

Vinyl siding and white vinyl soffit

16" eave on HE and Rear; 18" on long walls

Nominal 4/12 pitch roof (Peak Sections)

30-year architectural fiberglass shingles

7/16" roof sheathing

Exterior GFI receptacle – front door

Separate receptacle for heat tape

Engineered roof trusses to 2.7 KPA snow load

2x10 floor joists @ 16" o.c.

3/8" wall sheathing on inside & outside of exterior walls

Insulation: R22 walls; R40 ceiling; R48 floor

2x6 side walls at 24" o.c. - 8' walls

19/32" T&G subfloor

Exterior Frost-free tap – kitchen sink

12" tubular steel frame with detachable hitches

Siding installed on HE and Rear with smart start divider

EXTERIOR DOORS

Insulated steel exterior doors, 36" front and rear

(where possible) with peepholes and deadbolts

Lever door handles

Coach lights at all exterior doors

WINDOWS

LowE PVC windows and sills with screens

KITCHEN

Adjustable shelf in all cabinets – (2) upper and (1) lower

Double stainless-steel sink

15" bank of drawers

PVC cabinet doors

2-speed range hood with light and fan vented to exterior

18 cu. ft. fridge

30" electric range

White kitchen appliances

Shelf over fridge

2 handle faucets

Communication box (empty) at kitchen area

UTILITY ROOM

Plumbed and wired for washer/dryer

High efficiency gas furnace

100-amp electrical panel

Electric hot water tank

Shelf over washer/dryer area

Dryer vent rough in

Insulated lines in HWT cavity

BATHROOMS

Exhaust fan with humidistat in main bath

Exhaust fan in ensuite on separate switch

Towel bar and towel ring (most models) in each bath

Cosmetic box in main bath

Showerhead and shower rod in all baths

GFI receptacle in all baths

Walled tub/shower with single lever pressure balanced

faucet in all baths

2 handle faucets in all baths

INTERIOR

Decorative vinyl covered drywall (one colour throughout)

6 mil. vapour barrier includes switches and receptacles

Quality vinyl floor covering throughout

Cathedral ceilings in LR, DR, KIT

Swirl light in dining room

Wire only ceiling light in living room

Ceiling lights in all rooms

Solid shelving in all closets

Knob handles on all doors

Factory select décor and lighting

White hardboard passage doors 24"-30" (no profile)

4" ceramic tile backsplash at kitchen and vanities with tile edging

2x4 interior walls

Vinyl wrap moulding throughout

MISCELLANEOUS

Electric smoke/CO detector(s)

Main electrical conduit through floor

Programmable thermostat

Airtight Protocol

LIMITED OPTIONS AVAILABLE

CUSTOM CHANGES ARE NOT PERMITTED

ALL HOMES ARE BUILT TO MEET OR EXCEED

CSA A-277 SPECIFICATIONS

ENERGY ZONE UPGRADES MAY BE REQUIRED

HOME IS BUILT TO MEET ENERGY ZONE 7A

ALL PRICES ARE F.O.B. LETHBRIDGE, AB

ALL PRICES DO NOT INCLUDE GST

ALL PRICES DO NOT INCLUDE ASSOCIATION FEES

STANDARDS IN EFFECT AS OF Jun 1, 2022

This is not a fully detailed specification. SRI Homes - Regent reserves the right to change specifications, designs, materials and suppliers without notice and without incurring obligation. Information contained herein is from data available at the time of printing